

Tattoo²

Go badge, print yourself!



Color & Monochrome Thermal Transfer



300 dpi



Single-sided



100 cards



0.25-0.76 mm (10-30 mil)



1 year

evolIS

www.evolis.com

Compact size, ease of use, core features and cost efficiency.

Tattoo² is the best deal for printing plastic cards on a small scale and for mobile applications.

In a few seconds, **Tattoo²** personalizes in monochrome or colour your pre-printed or blank plastic cards.

With a 300 dpi standard resolution and 'near-to-edge' printing, **Tattoo** prints pictures, texts, barcodes and logos as required.

Tattoo² is a flexible solution which offers a dual card-feeding mode. Cards can be loaded automatically thanks to the 100-card feeder but you can also use the manual loading mode for on-demand delivery.

It also features a detachable output hopper to collect printed cards.

Sleek and with a contemporary look, **Tattoo²** is today the most compact plastic card printer in its category.

It squeezes into any location: offices, reception desks, and even shop counters.

Tattoo² fully addresses the specific needs of small organizations that print badges in low volume or just once in a while: sport clubs, SMEs, retail outlets, schools, libraries and local authorities

It is ideal for membership cards, subscription and loyalty cards, badges for visitors and employees and much more.

Go badge, print yourself!

GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection
- 16 MB RAM
- Detachable feeder with a capacity of 100 cards (30 mil or 0.76 mm)
- Detachable output hopper with a capacity of 15 cards (30 mil or 0.76 mm)
- 1-Button and 4-LED control panel
- Available in Fire red color
- Automatic card thickness adjustment

CARD LOADING MODES

- Automatic with feeder and/or hand-feed

PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Integrated ribbon saver for monochrome printing

PRINTING SPEED

Personalization throughput will depend on card design and printer settings

- Color (YMCKO): 40 sec/card¹
- Monochrome: 7 sec/card¹

SUPPORTED PLATFORMS

- Windows™ XP, Server 2003 and Vista 32 & 64 bits

SUPPLIED SOFTWARE

- eMedia Trial - 30 days evaluation

RIBBON TYPES

- 5-panel YMCKO color ribbon - up to 100 cards/roll
- Monochrome ribbons - Up to 600 cards/roll: available in black, red, green and blue - Up to 500 cards/roll: available in white, gold and silver
- BlackWAX monochrome ribbon (for ABS & special varnished plastic cards) - up to 600 cards/roll

OPTIONS / ACCESSORIES

- 100-card additional feeder
- Cleaning kits

WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer

- Printer, print head: 1 year warranty, unlimited number of passes²



- Card types
- Card format
- Card thickness
- Card feeder capacity
- Card output hopper capacity
- Printer size
- Printer weight
- Connections
- Electrical
- Environmental

- All PVC, Composite PVC cards, PET, ABS¹ & varnished¹ cards
- ISO CR-80 - ISO 7810 (3.375" x 2.125" - 53.98 mm x 85.60 mm)
- From 10 mil (0.25 mm)³ to 30 mil (0.76 mm)
- 100 cards (30 mil - 0.76 mm), 300 cards (10 mil - 0.25 mm)
- 15 cards (30 mil - 0.76 mm), 45 cards (10 mil - 0.25 mm)
- Height: 6.53" (166 mm) - Length: 11.42" (290 mm) / 14.49" (368 mm) with the detachable hopper
- Width: 7.36" (187 mm)
- 5.3 Lbs (2.4 Kg)
- USB (Cable supplied)
- Power supply: 110-230 Volts AC, 1,8 A, 60-50 Hertz
- Printer: 24 Volts DC, 3 A
- Min/Max operating temperature: 59° / 86° F (15° / 30°C)
- Humidity: 20% to 65% non-condensing
- Min/Max storage temperature: 23° / 158° F (-5° / +70°C)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

1. Under specific conditions
 2. Subject to observance of specific conditions and use of Evolis Genuine Consumables
 3. 10 mil cards must be used only for monochrome printings



AMERICAS
Evolis Inc.
 1835 South Perimeter Road
 Suite 190 - Fort Lauderdale
 FL 33309 - USA
 Tel: (954) 491-9898
 Fax: (954) 491-5140
 evolisinc@evolisc.com

EUROPE, MIDDLE EAST, AFRICA
Evolis Card Printer
 14, avenue de la Fontaine
 Z.I. Angers Beaucaouzé
 49070 Beaucaouzé - France
 Tel: + 33 (0) 241 367 606
 Fax: + 33 (0) 241 367 612
 info@evolisc.com

ASIA PACIFIC
Evolis Asia Pte Ltd
 120 Lower Delta Road
 #13-12 Cendex Centre
 Singapore 169208
 Tel: +65 6377 9731
 Fax: +65 6278 7002
 evolisasia@evolisc.com