

# 2-inch Kiosk printer

# NP-2411

NEW



## Features

- Lock free cutter
- Low profile
- Small footprint
- Simplified design



## Application

- Photo kiosk
- Parking system, etc.

## Specifications

Model	NP-2411
Print method	Line thermal dot
Paper width / Print width	58 , 60 mm / 52, 54mm
Print speed	Max.150mm/sec.
Resolution	8dots/mm
Character size (dot x dot)	FontA(12x24):1.50x3.00mm,FontB(9x17):1.13x2.13mm
Character type	ANK, Japanese, Extend graphic character set, International, Korean, Chinese (GB18030-2000), Greek, Polish, Russian, Scandinavian, Turkish
Barcode	UPC-A,UPC-E, JAN13(EAN), JAN8(EAN), CODE39, ITF, CODA BAR, CODE128
Line feed pitch	0.125mm
Interface	Serial (RS-232C) & USB (V2.0 FULL SPEED)
Input buffer	Approx. 10K bytes
Operating voltage	DC24V ± 5%
External dimensions	103.6(W) x 123.5(D) x 77.3(H)mm
Weight	500g
Paper type	Thermal paper (max. 83mm in diameter)
Operating temperature	-15 ~ 60
Storage temperature	-20 ~ 60
Reliability (head)	100km
Auto cutter	1 million cuts, Full cut and Partial cut *Command selectable
Safety regulation, EMC standard	CE, UL60951-1, VCCI: Class A, FCC: Class A

2-inch

Auto loading

Openable head

Auto cutter