

NEW!

HECON[®]

HENGSTLER

X-56™ Thermal Printer

Versatile, Flexible and Robust!



**Perfect for Ticketing,
Receipts and more!**

- **Fast USB or serial interface**
- **Prints up to 250 mm/second**
- **Prints/cuts stock over 250 g/m²**
- **Autocutter with jam sensor**
- **Optional presenter**
- **Optional sleep mode ideal for remote, battery operation charged by solar cells**
- **Wide voltage range option allows operation from 10-39 volts, ideal for use on vehicular electrical systems.**

The HECON/Hengstler X-56 Thermal Printer is one of the most versatile printers around! Handling a paper width of 49-60 mm, the X-56 printer prints at speeds up to 250 mm/second (9.8 inches/second)! An autocutter is standard, with versions that can cut up to 300 g/m² paper stock. The design includes an integral chute that protrudes from the front of your panel, making mounting and integration simple. A jam sensor detects paper jams and stops printing. Optional sleep mode will put the printer to sleep, where it uses only microamps of current. This is important in remote, solar cell charged battery systems. An optional wide voltage range allows connection to almost any vehicle's electrical system, while the X-56's wide range of paper stock thicknesses makes it ideal for printing heavy tickets. A presenter is available where needed to prevent vandalism.

Have a narrow printer need? Take a look at the HECON/Hengstler X-56!

extendo
plug + print

HECON/Hengstler X-56™ Thermal Printer

Applications

Just a few typical applications for the X-56 include the following:

Parking: Often powered by batteries charged by solar cells, streetside parking systems are ideal for the X-56 due to the optional sleep mode. This reduces power consumption to almost nothing, greatly decreasing the average current needed to keep the system “alive” and decreasing power requirements. And the wide temperature and humidity range are perfect for outdoor operation

Ticketing: Because the X-56 is able to print and cut very heavy paper stock, it does an excellent job with ticketing, where thicker, more durable printouts are the norm. And this all fits in a compact package that takes up little room inside the kiosk or dispenser.

Mobile Operation: Whether it's for transit fare receipt printing, or invoices for fuel oil delivery, the X-56 is at home when on the go! With a voltage range that covers virtually any motor vehicle and vibration protection to match, the X-56 is your choice when printing is needed in your vehicle.

Reverse Vending: Those recycling machines are here to stay, especially as states become increasingly environmentally responsible. It's critical to be able to produce a receipt reliably, and with confirmation that the receipt has been taken. After all, it's money; take it to the cashier, and you get cash back. The chute sensor in the X-56 let's you do exactly that.

Kiosks: Used for almost any application today, kiosks have become ubiquitous. From loyalty programs to online ordering to configuring your sub sandwich, kiosks are here to stay. And the X-56 is the ideal partner for them. With an optional presenter to prevent vandalism, high print speed, fast USB or serial interface, available chassis configurations, and much more, the X-56 is flexible enough to meet the widely varying demands of the kiosk industry!

Specifications

Technology:	Direct Thermal
Print Speed:	Up to 9.8 ips (250 mm/sec)
Resolution:	203 dpi (8 dots/mm)
Printhead Life	
<i>Abrasion (based on 12.5% print density)</i>	100 km of paper
<i>Electrical:</i>	100 million dot pulses
Graphic Driver:	Windows® 2000/XP, Linux
Bar Codes:	
<i>Internally Generated:</i>	UPC-A, UPC-E, EAN-13, EAN-8, Code 39, Interleaved 2 of 5, Code 128, Codabar, PDF 417
<i>Externally Generated:</i>	Any, generated by Windows® standard GDI file by host
Paper Width:	1.93 to 2.36 inches (49-60 mm)
Printable Width:	2.20 inches (56 mm)
Paper Weight:	50 to 250 g/m ² (higher in some cases)
Paper Capacity:	6 inch (150 mm) roll diameter 12 inch (300 mm) <small>(reduced performance)</small>
Interface Type:	USB 1.1 or RS-232
Serial Baud Rate:	9,600 to 115,200 baud
Operating Voltage:	24 VDC± 5% 12 VDC (11-15 VDC) 10-39 VDC nominal (optional)
Power Consumption:	
In standby, approx.	3.6 VA
Sleep mode (optional)	<50 µA
Typical, approx.	Print speed dependent
Peak, approx.	Print speed dependent
Cutter:	Guillotine (full or partial cut) or Rotary Type (heavy stock)
Presenter (optional):	Loop-type
Dimensions (WxHxD):	100 x 100 x 100 mm (approx.)
Temperature Range	
<i>Operating:</i>	-25°C to +70°C
<i>Storage:</i>	-30°C to +75°C

Also available in configurations with integral chassis and paper holder.

extendo
plug + print

All specifications subject to change without prior notice.
“HECON” is a registered trademark of Danaher Corporation.
“Windows” is a trademark of Microsoft Corporation.

Copyright © 2007 HECON/Hengstler/Danaher Sensors & Controls Group

HECON®
HENGSTLER

2100 West Broad Street Elizabethtown, NC 28337
Phone: (866) 394-3626 or (732) 528-7101 Fax: (732) 528-4999
Web: www.hecon.com Email: info.hecon@hecon.com

April 13, 2007