

NP-G30

3-inch

**Solid and Durable structure
Built in Paper Presenter**



Paper arm "UPH-Arm200" is an option.

= OPTIONAL PARTS =

Reverse insertion prevention connector



Power supply PS11-U3/E3

A reverse insertion prevention connector is bundled.



Paper arms



UPH-Arm150



UPH-Arm200

Model name	NP-G30D	
Print method	Direct line thermal dots	
Print speed	Max. 200mm/sec.	
Resolution	8dots/mm(203dpi)	
Gradation	16 gray scale	
Number of dots/line	576dots	592dots
Paper width	80mm	82.5mm
Print width	72mm	80mm
Paper diameter	Max.φ200mm (option)	
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Japanese	
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, CODE93, GS1 DataBar, PFD417, QR code (model2), Linked QR code (model2), Micro QR code	
Interface	USB(V2.0 full speed) and Serial(RS232C)	
Cutter	Full cut	
Operating voltage	DC24V	
External dimensions	121.2(W) x155.7(D) x72(H) mm (w/o paper arm) 134.2(W) x303.5(D) x129.4(H) mm (with UPH-Arm200 and a roll paper 200mm O.D.) 125.8(W) x266.9(D) x109.7(H) mm (with UPH-Arm150 and a roll paper 150mm O.D.)	